



LTL3500

Specifications

Optical specifications

Field of measurement:

- Width: 50 mm / 2 inch
- Height: 180 mm / 7.1 inch

Illumination angle R_L EN 1436: 1.24°

Illumination angle R_L ASTM E 1710: 88.76°

Observation angle R_L EN 1436: 2.29°

Observation angle R_L ASTM E 1710: 1.05°

Illumination angle Qd: Diffuse

Illumination angular spread:

- Horizontal: / Vertical: 0.33 / 0.17°

Observation angular spread: $\pm 0.17^\circ$

Equivalent observations distance: 30 m

R_L range (mcd·m-2·lx-1) 0 - 4000

Qd range (mcd·m-2·lx-1) 0 - 318

Instrument dimensions

Length: 470 mm / 18.0 inch

Width: 150 mm / 5.9 inch

Height: 280 mm / 11.0 inch

Weight: 5.6 kg / 12.3 lbs

Construction

Structural parts: Aluminum

Housing: Polymer

Keyboard: Silicone rubber & touch screen

Display

- 5" high brightness color touch display
- Resolution 800 x 480 pixels

Macro camera, overhead camera

- Macro camera for close-up pictures of markings
- Overhead camera for overview of markings
- Resolution 5 megapixels (2592 x 1944 pixels)

Regulatory compliance

EU:

Radio: EN 303-413 V1.1.1:2017

EMC: EN 301-489-19 V2.1.1 (2019-04)

Safety: IEC 61010-1:2010, AMD1:2016; EN 61010-1:2010+A1:2019

USA:

FCC: 47 CFR Part 15B (class B)

Canada:

ICES-003:2016 (Class B)

Electrical characteristics

Power supply:

Battery: Rechargeable and replaceable Li-Ion 12V 3.0 Ah

Charging time: Approx. 1 hour 15 min.

External chargers:

- 230 V / 50 Hz
- 120 V / 60 Hz

Data

Data memory: 8 GB

Data transfer: USB 2.0, Wi-Fi

Typical repeatability: $\pm 2\%$

Typical reproducibility: $\pm 5\%$

Environmental specification

Temperature:

- Operating: 0°C to +60°C / 32°F to 140°F
- Storage: -10°C to +60°C / 14°F to 140°F
- Humidity: 20 - 85%, non-condensing
- Altitude: 4000 m / 13.000 feet

Timing

Measurement time: <1 sec.

Standards

EN 1436 (R_L & Qd), ASTM E1710 (R_L), ASTM E2177 (R_L wet), ASTM E2302 (Qd), ASTM E2367 (night colors), ASTM 2832 (continuous wetting)

General features

- R_L and Qd for dry & wet markings as well as continuous wetting (R_L only)
- Measurement time 1 sec (R_L & Qd)
- Measures R_L on profiled markings up to 15 mm / 0.6 inch
- Memory capacity 8GB
- Multi-lingual menu
- Average calculation
- Easy-readable color touch LED display with 3 buttons
- Long-life illumination system
- USB memory stick & WiFi interface, IOT prepared
- Power supply, standard Bosch professional battery
- Shows and stores date, time, air & marking temperature and humidity
- Facility for entering and storing road ID, user ID and other measurement related data
- Road icon reference
- Data presentation in Excel and Google Earth
- Stray light compensated
- Single handed operation, user-friendly

Optional features

- Qd
- GNSS positioning
 - Latitude / Longitude format: Decimal degrees
 - Datum: WGS 84
- Nighttime color (x,y) for R_L measurements (white & yellow)
- Macro and overview cameras
- Orientation (compass, instrument tilt)
- External printer

Standard delivery

- LTL3500 Retroreflectometer
- Hard-case transportation box
- R_L calibration standard with DANAK certificate
- Qd calibration / verification marking (if Qd is ordered)
- Battery charger
- Quick guide
- USB memory stick

Downloads

User manual to be downloaded from www.roadsensors.com under 'Products' and 'User manuals':

Warranty

2 years

*R&TTE Declaration of Conformity (DoC) and US Attestation of Conformity (AoC) can be supplied by DELTA upon request or viewed on: roadsensors.madebydelta.com/technical-background/certification
Specifications may be changed without notice.*

